



Wall mounted unit

FTXZ-N + RXZ-N

BLUEEVOLUTION

Ururu
Sarara



Daikin Residential
Controller



3 area motion
detection sensor



Energy saving during
standby mode



Ururu -
humidification



Sarara -
dehumidification

Complete climate control with (de)
humidification, air purification & ventilation with
top efficiencies in heating & cooling

- › 5 Air treatment techniques in 1
- › 3 area motion detection sensor
- › Daikin residential controller via app
- › Voice control
- › Automatic filter cleaning

- › Full range A+++
- › Oh so quiet
- › 3-D airflow: air is blown into all corners of a room
- › Award winning design

FTXZ-N + RXZ-N



FTXZ-N



RXZ-N



ARC477A1

Indoor unit		FTXZ		25N	35N	50N
Dimensions	Unit	HeightxWidthxDepth	mm	295 x798 x372		
Weight	Unit		kg	15		
Air filter	Type			Auto cleaning filter		
Fan	Air flow rate	Cooling	Silent operation/ m³/min	4.0 / 5.3 / 10.7	4.0 / 5.6 / 12.1	4.6 / 6.6 / 15.0
		Heating	Silent operation/ m³/min	4.8 / 6.7 / 11.7	4.8 / 6.9 / 13.3	5.9 / 7.7 / 14.4
Sound power level	Cooling		dB(A)	54	57	60
	Heating		dB(A)	56	57	59
Sound pressure level	Cooling	Silent operation/Low/Nom./High	dB(A)	19 / 26 / 33 / 38	19 / 27 / 35 / 42	23 / 30 / 38 / 47
	Heating	Silent operation/Low/Nom./High	dB(A)	19 / 28 / 35 / 39	19 / 29 / 36 / 42	24 / 31 / 38 / 44
Control systems		Infrared remote control		ARC477A1		
		Wired remote control		-		

220V | 230V | 240V | Front of heat exchanger | Back of heat exchanger


Outdoor unit		RXZ		25N	35N	50N
Dimensions	Unit	HeightxWidthxDepth	mm	693 x795 x300		
Weight	Unit		kg	50		
Sound power level	Cooling		dB(A)	59	61	63
	Heating		dB(A)	59	61	64
Sound pressure level	Cooling	High	dB(A)	46	48	49
	Heating	High	dB(A)	46	48	50
Operation range	Cooling	Ambient	Min.~Max. °CDB	-10 ~43		
	Heating	Ambient	Min.~Max. °CWB	-20 ~18		
Refrigerant	Type			R-32		
	GWP			675		
	Charge		kg/TCO2Eq	1.34 / 0.9		
Piping connections	Liquid	OD	mm	6.35		
	Gas	OD	mm	9.5		
	Piping length	OU - IU Max.	m	10		
	Level difference	IU - OU Max.	m	8		
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50 /220-240		
Current - 50Hz	Maximum fuse amps (MFA)		A	16		

220V | 230V | 240V | Contains fluorinated greenhouse gases

Efficiency data			FTXZ + RXZ	25N + 25N	35N + 35N	50N + 50N	
Cooling capacity	Min./Nom./Max.		kW	0.6 /2.5 /3.9	0.6 /3.5 /5.3	0.6 /5.0 /5.8	
Heating capacity	Min./Nom./Max.		kW	0.6 /3.6 /7.5	0.6 /5.0 /9.0	0.6 /6.3 /9.4	
Power input	Cooling	Min./Nom./Max.	kW	0.11 /0.41 /0.88	0.11 /0.66 /1.33	0.11 /1.10 /1.60	
	Heating	Min./Nom./Max.	kW	0.10 /0.62 /2.01	0.10 /1.00 /2.53	0.10 /1.41 /2.64	
Space cooling	Energy efficiency class			A+++			
	Capacity	Pdesign	kW	2.50	3.50	5.00	
	SEER			9.54	9.00	8.60	
	Annual energy consumption			kWh/a	92	136	203
Space heating (Average climate)	Energy efficiency class			A+++			
	Capacity	Pdesign	kW	3.50	4.50	5.60	
	SCOP/A			5.90	5.73	5.50	
	Annual energy consumption			kWh/a	831	1,100	1,427
Nominal efficiency	EER			6.10 (1)	5.30 (1)	4.55 (1)	
	COP			5.80 (1)	5.00 (1)	4.47 (1)	
	Annual energy consumption			kWh	205	330	550
	Energy labeling Directive Cooling/Heating			A/A			

(1) EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



ECPEN21-021

01/2021



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

